



NO.	NAME OF PARTS	QTY	MATERIALS	SPECIFICATIONS
16	ELECTIC ACTUATOR	1	ASSEMBLY	
15	GLAND NUT	2	A194 2H	
14	GLAND BOLT	2	A193 B7	
13	GLAND FLANGE	1	A216 WCB	
12	GLAND	1	A276 410	
11	PACKING	1S	GRAPHITE	
10	BONNET NUT	1S	A194 2H	
9	BONNET BOLT	1S	A193 B7	
8	BONNET	1	A216 WCB	
7	BONNET GASKET	1	SS304+GRAPHITE	
6	STEM	1	SS304	
5	TOP CAGE	1	SS304	
4	PLUG	1	SS304	
3	CAGE	1	SS304	
2	SEAT GASKET	1	SS304+GRAPHITE	
1	BODY	1	A216 WCB	
1S=1 SET				
PERFORMANCE SPECIFICATION	NOMINAL PRESSURE	4.0MPa		
	SHELL TEST	60bar		
	SEAL TEST	44bar		
	LEAKAGE TEST	3.5bar		
	WORKING TEMPERATURE	-29°C~425°C		
	SUITABLE MEDIUM	W.O.G		
	FLOW CHARACTERISTIC			
	RATED CV			
TECHNICAL REQUIREMENTS	DESIGN STD.	IEC 60534-8-2-2011		
	END CONNECTION	ANSI B16.25-2009		
	FACE TO FACE OR END TO END	MANUFACTURE'S		
	LEAKAGE STD.	IEC 60534-4-2011		
	MATERIAL STD.	ANSI/ASTM A216-2004		
	PRESSURE-TEMPERATURE RATINGS	ANSI/ASME B16.34-2009		
VALVE TYPE	ELECTRIC CONTROL VALVE	CUSTOMER		
VALVE MODEL	T967H-40CG-DN100	PROJECT		
TAG NO.		ENQUIRY		
DRAWING NO.		ITEM		
DESIGNED BY		WEIGHT		
CHECKED BY		SCALE		
APPROVED BY		PAGE/TOTAL PAGE		
DATE APPROVED		EDITION	0	MARK DATA BY